






















Product quality		
<b>Format</b>		1207 x 216 x 9,4 mm
<b>Packaging</b>	<b>Pack:</b>	7 elements / 1.825 m <sup>2</sup> / 17.00 kg
	<b>Palette:</b>	36 packs / 65.700 m <sup>2</sup> / 627.00 kg
Tolerances (requirement EN 16511)		
<b>Squareness of the elements (≤ 0.20 mm)</b>		≤ 0,20 mm/m
<b>Determination of linearity (≤ 0.30 mm/m)</b>		≤ 0,15 mm/m
<b>Flatness concave / convex</b>	<b>lengthwise (≤ 0.50/≤ 1.0 %)</b>	≤ 0,35 / ≤ 1,0 %
	<b>wide (≤ 0.15/≤ 0.20 %)</b>	≤ 0,10 / ≤ 0,10 %
<b>Surface flushness</b>	<b>(average ≤ 0.10 mm)</b>	average ≤ 0.10 mm
	<b>(max. ≤ 0.15 mm)</b>	max. ≤ 0.15 mm
<b>Opening between installed elements</b>	<b>(average ≤ 0.15 mm)</b>	average ≤ 0.05 mm
	<b>(max. ≤ 0.20 mm)</b>	max. ≤ 0.10 mm
Guarantee (According Parador guarantee conditions)		Notes
Domestic area	Commercial area	- not suitable for all-over adhesion
15 years	5 years	- cleaning and maintenance see instructions
		- technical changes reserved
   		

Classification		
	Test method	Rating
 <b>Utility class 23</b> domestic areas with intensive use	EN 16511	Living room, hall, kitchen, home office
 <b>Utility class 31</b> commercial areas with low use	EN 16511	Hotels, small offices
 <b>Wear layer</b>	ISO 24340	0,3 mm
 <b>Surface Coating</b>		PUR
 <b>Reaction to fire</b>	EN 13501-1	B <sub>fl</sub> s1
 <b>Slip resistance</b>	EN 14041	μ ≥ 0,35 DS
 <b>Staining resistance</b>	EN 438-2	Category 1 + 2: level 4, slight change Category 3: level 3, moderate change
 <b>Light fastness</b>	EN ISO 105 – B02	Blue wool scale: Stage ≥ 6
 <b>Resistance to roller castor chairs</b>	EN 425	Type W, no visible changes
 <b>Thermal resistance</b> Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN ISO 10456	0,068 m <sup>2</sup> *K/W
 <b>Moving a furniture leg</b>	EN 424	No visible changes
 <b>Indentation-residual</b>	EN ISO 24343-1	≤ 0,10 mm
 <b>Formaldehyde emission (E1 = 0.1 ppm)</b>	EN 16516	≤ 0,05 ppm
 <b>Acoustical - Impact noise reduction</b>	ISO 717-2	15 dB (on Akustik-Protect 100) 16 dB (on PE film)
 <b>Abrasion</b>	prEN 15468 Annex A	≥ 1.500 rev.
 <b>Impact resistance</b>	EN 13329 Annex F	≥ 800 mm
 <b>Thickness swelling</b>	ISO 24336 (≤ 18%)	≤ 16%
<b>Antimicrobial activity</b>	ISO 22196	Antibacterial
<b>Slip resistance on an inclined plane</b>	DIN 51130	Brushed, wood texture: R9 / Vivid texture: R10
<b>Disposal</b>	EAK-Code-number	17 02 03

Changed:	QMB Parador	File:	PA_TDS_Designboden_Vinyl_Basic-30_EN_20210701
Date:	01.06.2012	Latest update at:	<a href="http://www.parador.eu/service/catalogue/download/technical-data-sheet">www.parador.eu/service/catalogue/download/technical-data-sheet</a>
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.07.2021