

Product quality			
<b>Formats</b>		856 x 403 x 5,5 mm	1290 x 196 x 5,5 mm
<b>Packaging</b>	<b>Pack:</b>	8 elements / 2.76 m <sup>2</sup> / 19.44 kg	8 elements / 2.023 m <sup>2</sup> / 14.34 kg
	<b>Pallet:</b>	30 packs / 82.792 m <sup>2</sup> / 598.14 kg	48 packs / 97.091 m <sup>2</sup> / 703.42 kg

Tolerances (Requirement EN 16511:2014+A1:2019)			
<b>Squareness of the elements (≤ 0.50mm)</b>		≤ 0,15 mm	
<b>Determination of Linearity (≤ 0.30 mm/m)</b>		≤ 0,20 mm/m	
<b>Flatness concave / convex</b>	<b>lengthwise (≤ 0.50 / ≤ 1.0 %)</b>	≤ 0,35 / ≤ 1,0 %	
	<b>wide (≤ 0.10 / ≤ 0.15 %)</b>	≤ 0,10 / ≤ 0,15 %	
<b>Surface flushness</b>	<b>(average ≤ 0.15 mm)</b>	(average ≤ 0.10 mm)	
	<b>(max. ≤ 0.20 mm)</b>	(max. ≤ 0.15 mm)	
<b>Opening between installed elements</b>	<b>(average ≤ 0.15 mm)</b>	(average ≤ 0.05 mm)	
	<b>(max. ≤ 0.20 mm)</b>	(max. ≤ 0.10 mm)	

Guarantee (according Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion
Lifetime	10 Years	- cleaning and maintenance see instructions
		- technical changes reserved



Classification		
	Test method	Rating
<b>Utility class 23</b> domestic areas with intensive use	EN 16511	Living room, hall, kitchen, home office
<b>Utility class 33</b> commercial areas with intensive use	EN 16511	Classrooms, open-plan offices, shops
Reaction to fire	EN 13501-1	C <sub>fl</sub> s1
Slip resistance	EN 13893 EN 14041	μ ≥ 0,30 DS
Staining resistance	EN 438-2	Category 1 + 2: level 5, no visible change Category 3: level 4, slight change
Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
Resistance to roller castor chairs	EN ISO 4918	Type W, no visible changes
<b>Thermal resistance</b> Suitable for installation over underfloor heating.	EN 12667	0,033 m <sup>2</sup> *K/W
Moving a furniture leg	ISO 16581	No visible damage (foot type 0)
Indentation-residual	EN ISO 24343-1	≤ 0,05 mm
Acoustical - Impact noise reduction	EN ISO 10140-3	17 dB
Locking strength	ISO 24334	lengthwise ≥ 1 KN/m transversely ≥ 1,5 KN/m
Abrasion	EN 15468 Annex A	> 7.000 rev.
Impact resistance	EN 13329 Annex F	≥ 1.800 mm
Dimensional stability	EN 16511	≤ 0,10 %
Micro scratch resistance	EN 16094	Method A MSR-A2
Slip resistance on an inclined plane	DIN 51130	R10
Disposal	EAK-Code-number	17 02 03
Suitable for damp rooms: 100% waterproof product construction enables use in damp rooms (please observe installation instructions).		

Changed:	QMB Parador	File:	PA_TDS_Modular-ONE_Hydron_EN_20230201
Date:	01.05.2021	Latest update at:	<a href="https://parador.de/en/services/downloads/design-flooring">https://parador.de/en/services/downloads/design-flooring</a>
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.02.2023